

	Rover	Traveler	Rambler	Tour II	Sportster	Tandem Pro
Frame Material	Hi-Ten Steel	4130 Chromoly Steel	4130 Chromoly Steel	4130 Chromoly Steel	6061 T6 Heat Treated Aluminium	4130 Chromoly Steel
Steering System	Direct	Direct	Direct	Linkage	Direct	Linkage
Seat Type	Chromoly Steel Frame	6061 T6 Aluminium Frame	6061 T6 Aluminium Frame	6061 T6 Aluminium Frame	6061 T6 Aluminium Frame	6061 T6 Aluminium Frame
Fore/Aft Seat Adjustment	11"	6"	13"	8"	9.5"	3" Front 7" Rear
Seat Recline	35-70°	40-60°	40-70°	45-70°	44-70°	50-70° Front 40-70° Rear
Boom Type	Adjustable Boom	Adjustable Boom	Adjustable Boom	3 Sizes	Adjustable Boom	3 Sizes
X-Seam Range	35"-50"	36"-46"	38"-54"	Short 40"-48" Medium 4"2"-50" Long 44"-52"	43"-53"	Short 37.5"-39.5" Medium 39.5"-41.5" Long 41.5"-43.5" Rear 35.5-42
Wheelbase Length	40"	44"	45"	41"	42"	92"
Overall Length (medium)	67.5"	73"	74"	71"	80"	122"
Track Width	30"	30.5"	30.5"	31.5"	31.5"	31"
Overall Width**	33"	34"	34"	34.5"	35"	34"
Folded Dimensions	N/A	42x32x22	N/A	N/A	N/A	N/A
Bottom Bracket Height	13"	13"	13"	13.5"	15"	14"
Seat Height	16.5"	15.5"	15.5"	12"	15"	11"
Total Weight (lbs.)	47(8 Sp Int) 48(NuVinci) 44(8 Sp Ext)	44(8 Speed) 43(Base) 43(GT)	37(8 Speed) 37(Base) 37.5(GT)	38(Base) 38.5(GT)	36(Base) 37(GT) 30(SL)	64
Combined Load Limit (lbs.)	400	300	300	300	250	450
Turning Dimensions*	9' 11" Diameter	9'6" Diameter	9' 11" Diameter	12' Diameter	9' 11" Diameter	36' Diameter
Component Levels Available	8 Speed External 8 Speed Internal NuVinci	Int 8 Spd Base GT	Int 8 Spd Base GT	Base GT	Base GT SL	Tandem Pro

COMPONENT GROUPS

	Single Speed	Internal 3	Ext 8 Speed	Int 8 Speed	NuVinci	Base
Drive System	Internal	Internal	Derailleur	Internal	Internal	Derailleur
Number of Speeds (Stock)	1	3	8	8	CVT	24
Gear Inch Range	24	24-43	24-66	20-53 (SRAM) 20-62 (Nexus) 25-80 (SA)	20-72	19-90 (20") 26-123 (26")
Pedals Type	Standard Platform	Standard Platform	Standard Platform	Standard Platform	Standard Platform	Standard Platform
Crankset/Rings	Alloy single 170mm 32t	RPM City Single 170mm 46t	Alloy Black 170mm 38t	Rover/Rambler 170mm 32t Traveler 170mm 38t	Alloy Black 170mm 42t	FSA Tempo Triple 170mm 30/42/52t
Bottom Bracket	Square taper	Square taper	RPM Sealed Square Taper	RPM Sealed Square Taper	RPM Sealed Square Taper	RPM Sealed Square Taper
Chain Type	KMC Single Speed	KMC Single Speed	KMC Z72 8 Speed	KMC Z72 8 Speed	KMC Z72 8 Speed	KMC Z72 8 Speed
Front Derailleur	N/A	N/A	N/A	N/A	N/A	microSHIFT FD-R438 Triple
Rear Derailleur	N/A	N/A	microSHIFT RD-M45L 8 Sp	N/A	N/A	microSHIFT RD-M45L 8 Sp
Cassette Size	17t, 19t or 25t cog	N/A	Sram PG-830 11-30 8 Speed	18t Cog (SRAM) 16t Cog (Nexus) 25t Cog (SA)	20t Cog	Sram PG-830 11-30 8 Speed
Shifters Set	Sturmey Archer twist shift	SL-3S42E NEXUS REVO SHIFTER 1300MM	microSHIFT DS85-8 Twist	Twist shifter	NuVinci CVT Shifter	microSHIFT DS85-8 Twist
Brake Levers	Promax Linear Pull, Locking	Promax Linear Pull, Locking	Promax Linear Pull, Locking	Promax Linear Pull, Locking	Promax Linear Pull, Locking	Promax Linear Pull, Locking
Brake Set	Zoom Mech. Disc	Zoom Mech. Disc	Alhonga Mechanical	Alhonga Mechanical	Alhonga Mechanical	Alhonga Mechanical
Wheel Set	TerraTrike Silver Single Wall	TerraTrike Silver Single Wall	TerraTrike Silver Single Wall	TerraTrike Silver Single Wall	TerraTrike Black Single Wall	TerraTrike Silver Single Wall
Tires/Size	CST Reflective 40 PSI 20 X 1.75	CST Reflective 40 PSI 20 X 1.75	CST Reflective 40 PSI 20 X 1.75	CST Reflective 40 PSI 20 X 1.75	CST Reflective 40 PSI 20 X 1.75	CST Reflective 40 PSI 20 X 1.75
Available On These Frame Models	Rover	Rover	Rover	Rover Rover Tandem Traveler Rambler	Rover	Traveler Rambler Tour II Sportster

COMPONENT GROUPS cont.

	Elite	Pro	GT	SL	Tandem Pro
Drive System	Derailleur	Derailleur	Derailleur	Derailleur	Derailleur
Number of Speeds (Stock)	27	27	27	18 or 27	27
Gear Inch Range	23-90	23-90	18-90 (20") 23-120 (26")	29-125 (18) 22-122 (27)	18-90
Pedals Type	standard platform	Shimano SPD Clipless	Standard Platform	None	Standard Platform
Crankset/Rings	Hollow forged FSA triple 170 30/42/52	FSA Gossamer MegaExo 170 30/42/53	FSA Vero Hollow Triple 170mm 30/42/52t	FSA SL-K Light Carbon Triple 170mm 30/42/52t	FSA Gossamer MegaExo 170mm 30/42/52t
Bottom Bracket	RPM sealed cartridge square taper	Integrated in crankset	RPM Sealed Square Taper	Integrated MegaExo	Integrated MegaExo
Chain Type	KMC Z9000 9 speed	KMC X9	KMC Z99 9 Speed	KMX X9 9 Speed	KMC X9 9 Speed
Front Derailleur	Shimano Tiagra or Sora triple	Shimano Ultegra	microSHIFT FD-439 Triple	Shimano Ultegra	microSHIFT FD-439 Triple
Rear Derailleur	Shimano Tiagra. Wide range option comes with LX long cage	Sram X.9	Shimano SLX M662 or Sram X7	Sram X0	Shimano XT M772
Cassette Size	Shimano HG50 9 speed. Wide range option 11-32 9 speed	Sram X.9 11-32 9 speed	Sram PG-950 11-32 9 Speed	Sram PG-980 11-34 9 Speed	Sram PG-950 11-32t 9 Speed
Shifters Set	Shimano Dura Ace bar end (optional Grip Shift)	Sram X.9 Grip Shift (optional Thumb Shifter)	Sram Attack or SRAM X7 Gripshift	Sram X0 Gripshift	Shimano Dura Ace Bar End
Brake Levers	Avid Linear Pull	Avid Linear Pull	Promax Linear Pull, Locking	Promax Linear Pull, Locking	Promax Linear Pull, Locking
Brake Set	Avid BB-5 mechanical disc	Avid BB-5 mechanical disc	Avid BB7 Mechanical	Avid BB7 Mechanical	Avid BB7 Mechanical
Wheel Set	WizWheelz silver machine built w/ black hubs	Velocity AeroHeat hand built	TerraTrike Black Double Wall	Velocity Aeroheat w/ bladed spokes	Velocity AeroHeat
Tires/Size	Schwalbe Marathon w/reflective strip 20 x 1.5 (406)	Schwalbe Marathon w/reflective strip 20 x 1.5 (406)	Schwalbe Marathon 20 X 1.5	Schwalbe Durano 20X1.1 Front, 26X1.1 Rear	Schwalbe Marathon 20 X 1.5
Available On These Frame Models	Traveler Rambler Tour II Sportster	Traveler Rambler Tour II Sportster	Traveler Rambler Tour II Sportster	Sportster	Tandem Pro

All Dimensions In Inches. Specifications and Components Subject To Change Without Notice.

* Turning Dimensions are from the centerline of the trike. NOTE: The fore or aft setup of the seat may change the turning dimensions slightly.

** Can be up to 3" wider depending on position of horizontal handlebars.